

TOWNSHIP OF MILLSTONE

Construction Department

County of Monmouth
Dennis Gibson, Construction Official

470 Stagecoach Road Millstone Township, NJ 08510 Phone (732) 917-2953 Fax (609) 208-2083

HOMEOWNER POOL CERTIFICATION

| вьоск | LOT | |
|--|--------------------------|---|
| In accordance with N.J.A.C. 5:23-2 Certificate-of-Approval has been iss | | USED IN WHOLE OR IN PART UNTIL A ficial. |
| · · | | built. I further certify that the pool will not be he Construction Official has issued |
| I have read the fence requiremen | ts listed below and unde | erstand them. |
| | Owner's Signature | |
| | Print name | |
| Sworn and subscribed to before me | this day of | 20 |
| Notowy signature | | |
| Notary signature | | |

FENCE REQUIREMENTS

Barrier shall be a minimum of 48 inches above ground level. Openings <u>shall not</u> be greater than 4 inches for vertical balusters with horizontal concentrated load of 200 pounds applied on a 1-square-foot area at any point of fence. Maximum mesh size for chain link fencing <u>shall not</u> exceed 1 ¼ inches square. Where the barrier is composed of horizontal and vertical members and the distance between the tops of the horizontal members is less than 45 inches (1143mm), the horizontal members shall be located on the swimming pool side of the fence. Spacing between vertical members <u>shall not</u> exceed 1 ¾ inches (44mm) in width.

Pedestrian gates <u>shall</u> open outward only, away from the pool, and <u>shall</u> be self-closing with a self-latching device. If the self-latching device is located less than 54 inches from the bottom of the gate then the release mechanism <u>shall</u> be located on the pool side of the gate at least 3 inches below the top of the gate. The gate and the barrier <u>shall not</u> have an opening greater than ½ inch within 18 inches of the release mechanism.